

GLOBAL EAST ASIA TECHNOLOGY CO.,LTD

5G Wall Mount Antenna

GL7038V-8

Applications:

- 1. Indoor distributed antenna system.**

Features:

- 1. Light weight, small size, wide bandwidth;**
- 2. Anti-ultraviolet ABS radome.**



www.global-antenna.com

info@global-antenna.com

86-371-58561629

Add: ROOM 1124, BLOCK C, CHAOLIUMAO, High-Tech
District, Zhengzhou, China

Zip: 450001

Technical Index				
Frequency	MHz	698-960	1710-2700	3400-4000
Gain	dBi	5.5	7.0	8.5
Horizontal Beam width	°	80	65	55
Vertical Beam width	°	70	60	30
V.S.W.R		≤1.8	≤1.8	≤1.8
Polarization		Vertical		
Intermodulation IM3 (2x33dBm)		≤ -153		
Input Impedance	Ω	50		
Max Power	W	50		
Lighting Protection		DC ground		
Mechanical Index				
Connector type		N-F		
Antenna dimension mm		180×170×60		
Antenna Weight kg		0.4		
Antenna radome material		ABS		
Working Temperature		-40°C to +65 °C		
Mounting Hardware--mm		Φ 35 ~ Φ 60		
Rated Wind Velocity		60 m/s		